

# SEDIMENT FILTERS – 2” SEDIMENT TRAPPER MODELS UNIT WITH POLYESTER ELEMENT AND REPLACEMENT

## SPECIFICATIONS:

- These sediment trapper filters come with a reusable polyester filter element and are available with replacement screens in several mesh sizes.
- These filters are designed to support the flow capacity of the entire system.
- Sediment is visible through the clear filter cover and can be quickly removed by opening the ball valve at the bottom.
- The clear cover is easily removed for total cleaning. **(No tools are required—use of tools voids the warranty, hand tighten only.)**
- The filters feature a larger reservoir to hold more sediment, and the centrifuge spin-down design efficiently separates sediment.
- The unique element design traps sediment in the lower reservoir of the clear cover.
- The filter body is made from durable PVC material and features a 2” SLIP x SLIP connection.



No Lead



## RATINGS:

- Max. Operating Pressure: 150 PSI at 73°F

## RECOMMENDED FLOW RATES:

- Minimum Flow Rate: 18 gpm
- Maximum Flow Rate: 100 gpm

DIMENSIONS							
Unit With Polyester Element Part No.	Pipe Size	Mesh Size	Micron Size	Opening Size	Length	Width	Polyester Replacement Element Part No.
2-24ST-F	2"	24	711	0.028"	15"	6"	FS2-24ST
2-30ST-F	2"	30	533	0.021"	15"	6"	FS2-30ST
2-40ST-F	2"	40	381	0.015"	15"	6"	FS2-40ST
2-60ST-F	2"	60	254	0.010"	15"	6"	FS2-60ST
2-100ST-F	2"	100	152	0.006"	15"	6"	FS2-100ST
2-140ST-F	2"	140	104	0.004"	15"	6"	FS2-140ST
2-250ST-F	2"	250	61	0.0024"	15"	6"	FS2-250ST

MATERIALS LIST	
Part Name	Material
Body	PVC
O-Rings	Buna-N
Filter	Polyester
Cover	High Impact Polymer Resin
Flush Valve	Body: PVC, Seat: PTFE



315 Flindt Drive P.O. Box 392  
Storm Lake, Iowa 50588-0392 U.S.A.  
merrillmfg.com

(800) 831-6962  
(712) 732-2760  
Fax No. 1-800-ANYFLOW