

# ANTI-SEIZE/GASKET LUBE & THREAD SEALING COMPOUND AND TAPE



# ANTI-SEIZE/GASKET LUBE

## Gasket Lube for Sanitary Installation - Premium Assembly Lubricant/Preservative

Merrill Anti-Seize/Gasket Lube is specifically formulated to aid in the assembly and preservation of pitless adapters in water well casing applications. It incorporates USDA H-1 food grade anti-seize technology with elastomer preservation technology.

Merrill Anti-Seize/Gasket Lube is formulated with a unique blend of synthetics and white oil thickened with a food grade aluminum complex soap. The aluminum complex soap provides the highest level of water resistance with thermal stability. The blend of USDA H-1 fluids were carefully balanced to provide a wide range of gasket compatibility and lubricity.

The Antibacterial / Antifungal additive further extends life of the lubricant and reduces the potential for contamination.

Specifically designed to aid in the installation of pitless adapters, Merrill Anti-Seize/GasketLube can be used for other gasket installation applications. It can also be used for anti-seize applications where drinking water or incidental food contact is likely.

### Anti-Seize/Gasket Lube

Order Number	UPC Bar Code (Qty.1)	Container Size	Container	Ctn. Qty.	Approx. Weight
Ⓢ PAL100	6 42367 71704 9	1 lb.	Can	12	1.0 lbs
Brush top can in economical/professional size.					

#### Premium Assembly Lubricant / Preservative

- USDA H-1 approved
- Safe for drinking water or incidental food contact
- Antibacterial / Antifungal additive
- Safe on metal, plastics and most gaskets



## AQUA-SEAL Thread Sealing Compound - "To Eliminate Leaks"

MERRILL THREAD COMPOUND AQUA-SEAL is a slow drying, soft setting, non-hardening pipe thread compound. Recommended for on-site or assembly line work. Lead free. Will not harden in can. This compound is made with the highest quality materials and may be used for sealing threads on all metals, ABS, PVC, CPVC, nylon, and plastic piping systems. All information provided is based on laboratory testing, independent laboratory test results, and actual field experience.

### Thread Sealing Compound

Order Number	UPC Bar Code (Qty.1)	Container Size	Container	Ctn. Qty.	Approx. Weight
Ⓢ IG2	6 42367 02003 8	2 oz.	Tube	72	0.1 lbs
Ⓢ MASP05	6 42367 12953 8	8 oz.	Can	24	0.9 lbs
Ⓢ MASP1	6 42367 12952 1	16 oz.	Can	12	1.8 lbs

#### Thread Sealing Compound Features/Benefits


- Ideal for Stainless Steel
- Low Odor
- Non-Toxic
- Lead Free
- Heavy-Duty Industrial Grade



**PTFE Teflon® Thread Sealing Tape with Nickel & AQUA-SEAL working together**

- Provides a strong, tight seal for thread joints and easily disassembles
- AQUA-SEAL will flow and fill gaps between threads
- AQUA-SEAL is soft set, so will not crack and seals for years



 No-Lead

**FEATURES AND BENEFITS**

**A Contains NICKEL**

Flows and fill gaps between the rigid threads of stainless steel and no lead brass fittings. Nickel powder (not gray color) is needed like copper in drill lube.

**B High Density**

Won't "cut up" when wrapped around the sharp threads and can be stretched some when put on threads to stay in place. Use 4mm - heavy and can still be stretched.

**C Thicker**

Fewer wraps are necessary to assure a leak proof seal (2 wraps + thread sealant)

**D Compatible with quality thread sealant**








When a quality thread sealant like AQUA-SEAL is applied on top of the gray PTFE it flows and fills gaps between threads. Tape only - will not always do.

**E Tape & AQUA-SEAL**

Provides a strong, tight seal for thread joints and easily disassembles. AQUA-SEAL is soft set, so will not crack and seals for years.



**PTFE Teflon® Thread Seal Tape - Be sure to ask for quality tape with Nickel**

Order Number	UPC Bar Code (Qty.1)	Description	Thickness	Ctn. Qty.	Approx. Weight
Gray Thread Seal Tape for Stainless Steel with Nickel - High Density					
 PTFEGSS50260	6 42367 42133 5	1/2" x 260" Long	.004"	100	0.04 lbs
 PTFEGSS50520	6 42367 42131 1	1/2" x 520" Long	.004"	100	0.05 lbs
 PTFEGSS75260	6 42367 43257 7	3/4" x 260" Long	.004"	100	0.04 lbs
White Thread Seal Tape - High Density					
 PTFEWH50260	6 42367 42135 9	1/2" x 260" Long	.0035"	100	0.03 lbs
 PTFEWH50520	6 42367 42136 6	1/2" x 520" Long	.0035"	100	0.04 lbs
 PTFEWH75260	6 42367 42137 3	3/4" x 260" Long	.0035"	100	0.04 lbs
 PTFEWH75520	6 42367 42138 0	3/4" x 520" Long	.0035"	100	0.05 lbs



WARNING: This product meets Federal USA Drinking Water requirements but has not been specifically tested or approved as no-lead in the State of California.



© 2025 Merrill Manufacturing Form No. 2084.11  
315 Flindt Dr. | Storm Lake, Iowa 50588 | (800) 831-6962 | [merrillmfg.com](http://merrillmfg.com)