

1" NO LEAD BRASS UNION TANK TEES

SPECIFICATIONS:

- Tank tee connects the water line from the pump to the pressure tank plus all the extra tapings needed to complete installation.
- Several lengths available for use with various pressure tanks: 5-1/2", 11", and 13".
- Several tank connections available: 1" MIP, 1" FIP, 1" quick connect, 1-1/4" MIP, 1-1/4" FIP, 1-1/4" quick connect.
- Other tapings provided: front drain hole (1 or 2) 1/2" FIP for 1" size tees and (1 or 2) 3/4" FIP for 1-1/4" size tees.
- Lateral connections for pipe to and from tank: 1" MIP and 3/4" FIP, or 1-1/4" MIP and 1" FIP.
- All tank tees have two 1/4" FIP tapings on top of the tee, for pressure switch and pressure gauge.
- Tank tees are available as one piece, with O-ring union on tank leg or union as part of the tank connection nut.
- Long version tank tees available as all cast or fabricated with copper tube to give you the length needed.
- 41 different models of No Lead Brass Tank Tees for any model pressure tank or installation needs.



No Lead



C.A. Certified



CERTIFICATIONS:

- IAPMO CA. Certified

MATERIALS LIST	
Part Name	Material
Union Tank Tee & Solder Union Body	No-Lead Brass
O-Ring	NBR (Nitrile)

DIMENSIONS										
Part No.	Type	Tank Connection	Lateral	Drain Hole (Qty/Size)	L in.	W in.	H in.	O-Ring Size	Ctn. Qty.	Approx. Wt./Lbs.
BATNL100U	FAB	1" MIP	1" MIP & 3/4" FIP	(1) 1/2"	13.00	5.49	1.97	OR215	10	2.1
BATNL100UC	CAST	1" MIP	1" MIP & 3/4" FIP	(1) 1/2"	10.90	5.49	1.97	OR215	2	2.5
BATNL1002U	FAB	1" MIP	1" MIP & 3/4" FIP	(2) 1/2"	13.30	5.30	1.94	OR215	10	2.1
BATNL1002UC	CAST	1" MIP	1" MIP & 3/4" FIP	(2) 1/2"	10.91	5.52	2.09	OR215	2	2.5
BATNL1001UCS	CAST	1" MIP	1" MIP & 3/4" FIP	(1) 1/2"	5.50	5.31	1.99	OR215	4	1.7
BATNL1002UCS	CAST	1" MIP	1" MIP & 3/4" FIP	(2) 1/2"	5.50	5.42	2.05	OR215	4	1.7
*BATNL1002UCG	CAST	1" MIP	1" MIP & 3/4" FIP	(2) 1/2"	11.00	5.55	2.05	N/A	2	2.5

*Grounded metal to metal union.

MIP = Male Iron Pipe
FIP = Female Iron Pipe

SOLDER NO LEAD BRASS UNIONS					
Part No.	Size	L in.	W & H in.	Ctn. Qty.	Approx. Wt./Lbs.
SBUNL100	1"	2.42	1.91	1	0.6
SBUNL125	1-1/4"	2.59	2.21	1	0.8



315 Flindt Drive P.O. Box 392
Storm Lake, Iowa 50588-0392 U.S.A.
merrillmfg.com

(800) 831-6962
(712) 732-2760
Fax No. 1-800-ANYFLOW