

1" NO LEAD BRASS TANK TEES

SPECIFICATIONS:

- Tank tee connects the water line from the pump to the pressure tank plus all the extra tapings needed to complete installation.
- Several lengths available for use with various pressure tanks: 2-1/2", 4-1/2", 5", 11", and 14".
- Several tank connections available: 1" MIP, 1" FIP, 1" quick connect, 1-1/4" MIP, 1-1/4" FIP, 1-1/4" quick connect.
- Other tapings provided: front drain hole (1 or 2) 1/2" FIP for 1" size tees and (1 or 2) 3/4" FIP for 1-1/4" size tees.
- Lateral connections for pipe to and from tank: 1" MIP and 3/4" FIP, or 1-1/4" MIP and 1" FIP.
- All tank tees have two 1/4" FIP tapings on top of the tee, for pressure switch and pressure gauge.
- Tank tees are available as one piece, with O-ring union on tank leg or union as part of the tank connection nut.
- Long version tank tees available as all cast or fabricated with copper tube to give you the length needed.
- 41 different models of No Lead Brass Tank Tees for any model pressure tank or installation needs.



No Lead



C.A. Certified



CERTIFICATIONS:

- IAPMO CA. Certified

MATERIALS LIST

| Part Name | Material |
|---------------|---------------|
| Tank Tee Body | No-Lead Brass |
| O-Ring | NBR (Nitrile) |

DIMENSIONS

| Part No. | Type | Tank Connection | Lateral | Drain Hole (Qty/Size) | L in. | W in. | H in. | O-Ring Size | Ctn. Qty. | Approx. Wt./Lbs. |
|-------------|------|---------------------|---------------------|-----------------------|-------|-------|-------|-------------|-----------|------------------|
| BATNL100 | FAB | 1" MIP | 1" MIP & 3/4" FIP | (1) 1/2" | 11.00 | 5.46 | 1.55 | N/A | 20 | 1.5 |
| BATNL101C | CAST | 1" MIP | 1" MIP & 3/4" FIP | (1) 1/2" | 11.00 | 5.40 | 1.48 | N/A | 2 | 2.1 |
| BATNL1002 | FAB | 1" MIP | 1" MIP & 3/4" FIP | (2) 1/2" | 10.90 | 5.36 | 1.44 | N/A | 20 | 1.4 |
| BATNL100C | CAST | 1" MIP | 1" MIP & 3/4" FIP | (2) 1/2" | 11.13 | 5.49 | 1.54 | N/A | 2 | 2.0 |
| BATNL100CS | CAST | 1" MIP | 1" MIP & 3/4" FIP | (2) 1/2" | 4.49 | 5.65 | 1.56 | N/A | 5 | 1.2 |
| BATNL100CXS | CAST | 1" MIP | 1-1/4" MIP & 1" FIP | (2) 1/2" | 2.52 | 5.48 | 1.56 | N/A | 4 | 1.2 |
| BATNL100L | FAB | 1" MIP | 1" MIP & 3/4" FIP | (1) 1/2" | 14.06 | 5.43 | 1.36 | N/A | 10 | 1.7 |
| BATNL1002L | FAB | 1" MIP | 1" MIP & 3/4" FIP | (2) 1/2" | 13.80 | 5.33 | 1.38 | N/A | 10 | 1.6 |
| BATNL1002SF | CAST | 1" FIP | 1" MIP & 3/4" FIP | (2) 1/2" | 5.46 | 4.55 | 1.44 | N/A | 5 | 1.4 |
| BATNL100B | CAST | 1" MIP x Solder | 1" MIP & 3/4" FIP | (1) 1/2" | 2.75 | 5.44 | 1.55 | N/A | 4 | 1.0 |
| BATNL1002B | CAST | 1" MIP x Solder | 1" MIP & 3/4" FIP | (2) 1/2" | 2.98 | 5.37 | 1.55 | N/A | 4 | 1.0 |
| BATNL1025 | CAST | 1-1/4" MIP & 1" FIP | 1" MIP & 3/4" FIP | (1) 3/4" | 4.45 | 5.29 | 1.65 | N/A | 4 | 1.4 |
| BATNL10252 | CAST | 1-1/4" MIP & 1" FIP | 1" MIP & 3/4" FIP | (2) 1/2" | 4.27 | 5.88 | 1.64 | N/A | 4 | 1.3 |
| *BATNL100QC | CAST | Quick Connect | 1" MIP & 3/4" FIP | (2) 1/2" | 5.04 | 5.49 | 1.71 | OR220 | 2 | 1.2 |

*Quick Connect end for WELLMATE® Tanks.

MIP = Male Iron Pipe
FIP = Female Iron Pipe



315 Flindt Drive P.O. Box 392
Storm Lake, Iowa 50588-0392 U.S.A.
merrillmfg.com

(800) 831-6962
(712) 732-2760
Fax No. 1-800-ANYFLOW