

NO-LEAD BRASS BOILER DRAIN HOSE BIBB MODEL WITH ANGLE OUTLET

SPECIFICATIONS:

- The no-lead brass boiler drain hose bibb with an angled outlet features a compression neoprene seal disk, ensuring a secure and reliable seal.
- It is designed with a 3/4" hose threaded outlet set at a 30-degree angle for efficient water flow.
- The heavy cast iron handle adds durability for long-lasting performance.



No Lead



C.A. Certified



RATINGS:

- Max Pressure: 250 PSI
- Max Operating Temp: 160°F

CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS										
Part No.	Thread Size	Outlet Angle	L in.	W in.	H in.	ID in.	OD in.	Approx. Wt./Lbs.	Ctn. Qty.	Approx. Lbs./Ctn.
BBDNL50MA	1/2" MIP	30°	2.57"	2.09"	3.49"	0.77"	0.83"	0.5	12	5.9
BBDNL75MA	3/4" MIP	30°	2.49"	2.09"	3.51"	0.77"	1.05"	0.5	12	6.1
BBDNL75FA	3/4" FIP	30°	2.62"	2.09"	3.35"	0.77"	1.17"	0.5	10	5.0

MATERIALS LIST	
Part Name	Material
Nut	Hot Rolled
Name Plate	Aluminium
Handle	Cast Iron (Wheel), No-Lead Brass (Cross)
Packing Nut	No-Lead Brass
Packing	Buna
Bonnet	No-Lead Brass
Washer	304 Stainless Steel
Stem	No-Lead Brass
Seat Packing	Buna
Screw	No-Lead Brass
Body	No-Lead Brass