

NO-LEAD BRASS BALL VALVES

SPECIFICATIONS:

- These no-lead brass ball valves feature a full port ball design to ensure maximum flow.
- They allow for easy flow adjustment or positive shutoff.
- The chrome plated ball enhances durability, while the Teflon® seals provide a reliable and secure seal.



No Lead

RATINGS

- WOG Rating: 600 W.O.G.
- Max Temp: 212°F

DIMENSIONS							
Part No.	Thread Size	x Thread Size	L in.	W in.	H in.	Ctn. Qty.	Approx. Wt./Lbs.
BBVNL50	1/2"	x 1/2"	4.75	2.60	1.10	10	0.5
BBVNL75	3/4"	x 3/4"	5.10	3.10	1.50	10	0.7
BBVNL100	1"	x 1"	6.25	3.50	1.76	10	0.9
BBVNL125	1-1/4"	x 1-1/4"	6.75	4.00	2.20	10	1.6
BBVNL150	1-1/2"	x 1-1/2"	7.25	5.00	2.50	4	2.0
BBVNL200	2"	x 2"	8.00	6.25	3.38	4	3.5
BBVNL300	3"	x 3"	12.50	8.75	5.25	2	10.4
BBVNL400	4"	x 4"	14.875	9.00	7.00	1	17.5

MATERIALS LIST	
Part Name	Material
Valve Body	No-Lead Brass
Ball	Chrome Plated
Seals	Teflon®