

# NO-LEAD BRASS COMPACT TANK TEES

## SPECIFICATIONS:

- Perfect for limited space applications.
- Lower cost option with all tapings included.
- Tank tee connects the water line from the pump to the pressure tank plus all the extra tapings needed to complete installation.
- Lengths available for use with various pressure tanks: 2.5", 2.9".
- Tank connections available: 1" FIP, 1-1/4" FIP.
- Other tapings provided: front drain hole (1) 1/2" FIP for 1" size tees and (1) 3/4" FIP for 1-1/4" size tees.
- Lateral connections for pipe to and from tank: 1" FIP and 1-1/4" FIP.
- All tank tees have two 1/4" FIP tapings on top of the tee, for pressure switch and pressure gauge.
- 41 different models of No Lead Brass Tank Tees for any model pressure tank or installation needs.



No Lead



C.A. Certified



## CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS									
Part No.	Type	Tank Connection	Lateral	Drain Hole (Qty/Size)	L in.	W in.	H in.	Ctn. Qty.	Approx. Wt./Lbs.
BCTNL100	CAST	1" FIP	1" FIP	(1) 1/2"	2.5	2.58	1.81	5	0.7
BCTNL125	CAST	1-1/4" FIP	1-1/4" FIP	(1) 3/4"	2.92	2.91	2.25	5	0.9

MATERIALS LIST	
Part Name	Material
Tank Tee Body	No-Lead Brass