

INSERT FITTINGS – TEES

NO-LEAD YELLOW BRASS

SPECIFICATIONS:

- Crafted with precision engineering, this tee features a flat bottom, allowing your hydrant to rest on a sturdy base.
- Made from solid no-lead yellow brass, this fitting meets federal low lead regulations and offers an economical and easy-to-install solution for connecting well pumps or submersible pumps to flexible polyethylene pipes.
- Specifically designed for ground bury applications, it meets the highest standards for durability and safety.
- Featuring an insert barb x female NPT x insert barb design, it provides a secure and efficient pipe connection.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

CERTIFICATIONS:

- IAPMO CA. Certified

| DIMENSIONS | | | | | | | |
|------------|------------------------|-------|-------|-------|-----------|-------------------|--|
| Part No. | Insert Size x FIP Size | L in. | W in. | H in. | Ctn. Qty. | Approx. Lbs./Ctn. | |
| BTFNL75 | 3/4" x 3/4" | 5.29 | 1.38 | 1.43 | 10 | 6.0 | |
| BTFNL1075 | 1" x 3/4" | 5.73 | 1.77 | 1.48 | 6 | 4.5 | |
| BTFNL100 | 1" x 1" | 5.85 | 1.81 | 1.79 | 6 | 5.0 | |
| BTFNL125 | 1-1/4" x 1-1/4" | 6.79 | 2.26 | 2.12 | 4 | 6.0 | |