

# MALE ADAPTERS (LIGHT DUTY MODEL) NO-LEAD BRONZE – INSERT FITTINGS

## SPECIFICATIONS:

- Crafted with precision engineering, this no-lead bronze light-duty male adapter is designed to connect flexible polyethylene pipe to a barbed end and a female NPT thread to the male end, providing a secure and reliable connection.
- Made from durable, corrosion-resistant no-lead bronze, this fitting provides a lightweight, cost-effective solution while ensuring easy installation for connecting well pumps or submersible pumps to flexible pipes.
- Compliant with federal low lead regulations, this male adapter ensures both safety and durability in various plumbing applications.
- The insert barb x threaded design allows for a secure and efficient pipe connection.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified



## CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS						
Part No.	Insert Size	x MIP Size	L in.	W & H in.	Ctn. Qty.	Approx. Lbs./Ctn.
CRBMANL50	1/2"	x 1/2"	2.34	1.02	10	1.6
CRBMANL75	3/4"	x 3/4"	2.40	1.24	10	2.5
CRBMANL1075	1"	x 3/4"	2.43	1.38	10	3.0
CRBMANL100	1"	x 1"	2.97	1.57	10	4.0
CRBMANL2510	1-1/4"	x 1"	2.97	1.58	10	3.9
CRBMANL1025	1"	x 1-1/4"	2.78	1.96	10	4.5
CRBMANL125	1-1/4"	x 1-1/4"	2.80	1.94	10	4.0
CRBMANL150	1-1/2"	x 1-1/2"	2.80	2.21	5	2.8
CRBMANL200	2"	x 2"	3.10	2.77	5	4.3