## **SUBMERSIBLE CHECK VALVES NO-LEAD BRONZE (NO-SPIN POPPET)**

## **SPECIFICATIONS:**

- Crafted for durability, the valve body and poppet are cast from no-lead bronze.
- An abrasion-resistant O-ring is precision fitted to the poppet, ensuring a positive seal within a tapered, self-cleaning valve seat.
- A Delrin<sup>®</sup> guide bearing supports the poppet stem, ensuring smooth, noise-free, and long-lasting operation.
- Corrosion-resistant stainless steel components, including the spring and lock nut, enhance durability.
- Designed with a no-spin poppet, this check valve can be used next to the outlet of a submersible pump.
- It can be installed and operated in both vertical and horizontal positions.
- Each Merrill check valve is individually boxed.









## **RATINGS:**

Working Pressure: 200 PSI

Maximum Operating Temp: 190°F

|       | <br>     | <br> |
|-------|----------|------|
| OFDI  |          | 10-  |
| CERTI | <br>: () |      |
|       |          |      |

IAPMO CA. Certified

| MATERIALS LIST           |                               |  |  |  |  |
|--------------------------|-------------------------------|--|--|--|--|
| Part Name                | Material                      |  |  |  |  |
| Valve Body               | No-Lead Bronze                |  |  |  |  |
| Poppet                   | No-Lead Bronze                |  |  |  |  |
| Cup for Spring           | 304 Stainless Steel           |  |  |  |  |
| Spring                   | 304 Stainless Steel           |  |  |  |  |
| Lock Nut                 | 304 Stainless Steel           |  |  |  |  |
| O-Ring                   | NBR (Nitrile)                 |  |  |  |  |
| Delrin® Guide<br>Bearing | Delrin®<br>(Polyoxymethylene) |  |  |  |  |

| DIMENSIONS |                   |          |          |          |   |                     |                     |  |  |
|------------|-------------------|----------|----------|----------|---|---------------------|---------------------|--|--|
| Part No.   | MIP x FIP<br>Size | L<br>in. | W<br>in. | H<br>in. |   | Approx.<br>Wt./Lbs. | Master<br>Ctn. Qty. |  |  |
| CVMNL100   | 1" x 1"           | 3.54     | 1.86     | 1.84     | 1 | 1.0                 | 60                  |  |  |
| CVMNL125   | 1-1/4" x 1"       | 3.51     | 1.86     | 1.82     | 1 | 0.8                 | 60                  |  |  |



