

DRIVE WELL POINTS

SPECIFICATIONS:

- Drive well points are designed to be driven into all types of soil.
- The jacket over gauze construction is brazed to a perforated steel pipe, providing strength and durability.
- All well points have a stainless steel jacket and gauze, ensuring long-lasting performance and resistance to corrosion.
- The 1-1/4" drive well points are compatible with the 1-1/4" drive coupling and 1-1/4" drive cap, while the 2" drive well points work with the 2" drive coupling and 2" drive cap.
- Each drive well point is individually boxed.
- Additional sizes are available upon request – please call for pricing.
- **NOTE:** The approximate water yield is 3 gallons per minute per square inch of screen area.



No Lead

DIMENSIONS				
Part No.	Pipe Size	Pipe Length	Gauze	Approx. Wt./Lbs.
DWP1252460S	1-1/4"	24"	60	6.5
DWP1253060S	1-1/4"	30"	60	6.7
DWP1253660S	1-1/4"	36"	60	8.4
DWP1254860S	1-1/4"	48"	60	9.9
DWP1256060S	1-1/4"	60"	60	12.2
DWP1253080S	1-1/4"	30"	80	7.3
DWP1253680S	1-1/4"	36"	80	9.9
DWP1254880S	1-1/4"	48"	80	11.2
DWP1256080S	1-1/4"	60"	80	12.2
DWP2003060S	2"	30"	60	12.0
DWP2003660S	2"	36"	60	13.4
DWP2004860S	2"	48"	60	17.4
DWP2006060S	2"	60"	60	19.1
DWP2003080S	2"	30"	80	12.0
DWP2003680S	2"	36"	80	13.9
DWP2004880S	2"	48"	80	17.5

MATERIALS LIST	
Part Name	Material
Drive Point Head	Cast Iron
Pipe	Galvanized Cast Iron
Gauze Mesh	Stainless Steel
Jacket	Stainless Steel