

MERRILL PRESSURE TANKS

SPECIFICATIONS:

- Merrill offers flexible ordering options and pass on the manufactured price, regardless of quantity, when purchased with other Merrill products.
- Each tank features a stainless steel 3/4" male pipe thread connection, ensuring durability and reliability.
- With a maximum working pressure of 150 psi, it is suitable for a variety of applications.
- Designed for domestic water systems, the tank is lead-free to ensure safe water use.
- The precharge is set at 35 psi for optimal performance.
- Constructed from cold-rolled carbon steel, the tank is coated with a triple-layer electrostatic paint for superior corrosion resistance. The water chamber is made of 100% butyl rubber and lined with polypropylene, ensuring a long-lasting and safe interior.
- Merrill pressure tanks come with a six-year warranty.



No Lead

RATINGS

- Maximum Working Pressure: 150 PSI
- Precharge: Set at 35 PSI

MATERIALS LIST	
Part Name	Material
3/4" MPT Connection	Stainless Steel
Tank Body	Cold Rolled Carbon Steel
Exterior Coating	Triple Layer Electrostatic Paint
Water Chamber	100% Butyl Rubber
Linear	Polypropylene

DIMENSIONS		
Part No.	Description	Approx. Wt./Lbs.
H2PT2	2.1 Gallon Pressure Tank	4.5
H2PT4	4.5 Gallon Pressure Tank	8.0
H2PT6	6 Gallon Pressure Tank	