

GALVANIZED TANK TEES

SPECIFICATIONS:

- Made from galvanized ductile iron, the tank tees offer a balance of economy and strength.
- They include 1/4" NPT tappings for both a pressure switch and a pressure gauge.
- The threads are chamfered for easy pipe connection.



No Lead

DIMENSIONS								
Part No.	Tank Conn.	Lateral	Drain Hole	L in.	W in.	H in.	Ctn. Qty.	Approx. Wt./Lbs.
IAT1XB	1"	1"	1/2"	3.84	3.29	2.04	25	1.9
IAT751XB	1"	1"	3/4"	4.02	3.61	2.40	25	2.0
IAT100XB	1-1/4"	1"	1/2"	3.80	3.33	2.40	25	1.6
IAT75100XB	1-1/4"	1"	3/4"	3.84	3.33	2.42	25	2.0
IAT125XB	1-1/4"	1-1/4"	1/2"	3.96	3.59	2.38	25	2.4
IAT75125XB	1-1/4"	1-1/4"	3/4"	4.02	3.59	2.36	25	2.5
*IAT100B	1-1/4"	1"	1/8"	3.84	3.31	2.34	25	1.5
*IAT125B	1-1/4"	1-1/4"	1/8"	4.03	3.53	2.35	25	1.7
AT751002B	1"	1"	(2) 1/2"	5.88	2.95	2.30	48	2.0
AT751252B	1-1/4"	1-1/4"	(2) 3/4"	6.04	3.47	2.64	24	2.7

*1/8" NPT is for air valves used with galvanized tanks