

# INSERT FITTINGS – COUPLINGS

## NO-LEAD YELLOW BRASS

### SPECIFICATIONS:

- Crafted with precision engineering, this barb x barb coupling with hex ensures a seamless and secure pipe-to-pipe connection, setting the standard in precision and reliability.
- Made from no-lead yellow brass, this fitting provides an economical and easy-to-install solution for connecting well pumps or submersible pumps to flexible pipes.
- Compliant with federal low lead regulations, the no-lead yellow brass coupling ensures both safety and durability in various plumbing applications.
- Featuring an insert barb x insert barb design, it provides a secure and efficient pipe connection.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

### CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS							
Part No.	Insert Size	x Insert Size	L in.	W & H in.	Ctn. Qty.	Approx. Lbs./Ctn.	
IBCPNL50	1/2"	x 1/2"	Hex	3.60	0.83	10	1.0
IBCPNL75	3/4"	x 3/4"	Hex	2.85	0.88	10	1.8
IBCPNL100	1"	x 1"	Hex	2.83	1.10	10	2.0
IBCPNL125	1-1/4"	x 1-1/4"	Hex	2.84	1.41	10	3.4
IHBCPNL150	1-1/2"	x 1-1/2"	Hex	3.08	2.03	5	2.7
IHBCPNL200	2"	x 2"	Hex	3.07	2.55	5	4.3