

INSERT FITTINGS – FEMALE ADAPTERS

NO-LEAD YELLOW BRASS

SPECIFICATIONS:

- Crafted with precision engineering, this fitting is designed to connect flexible polyethylene.
- Made from no-lead yellow brass, this fitting provides an economical and easy-to-install solution for connecting well pumps or submersible pumps to flexible pipes.
- Compliant with federal low lead regulations, the no-lead yellow brass female adapter ensures both safety and durability in various plumbing applications.
- Featuring an insert barb x female pipe thread design, it provides a secure and efficient pipe connection.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified



CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS							
Part No.	Insert Size	x	FIP Size	L in.	W & H in.	Ctn. Qty.	Approx. Lbs./Ctn.
IBFANL50	1/2"	x	1/2"	2.57	1.19	10	2.8
IBFANL75	3/4"	x	3/4"	2.47	1.40	10	3.7
IBFANL100	1"	x	1"	2.66	1.69	10	5.4
IBFANL125	1-1/4"	x	1-1/4"	3.01	1.98	10	5.9