

INSERT FITTINGS – HYDRANT ELBOWS NO-LEAD YELLOW BRASS

SPECIFICATIONS:

- Crafted with precision engineering, this hydrant elbow is flat-sided to provide excellent support for your hydrant, ensuring stability and reliability.
- Made from high-quality no-lead yellow brass, it offers an economical and easy-to-install solution for connecting well pumps or submersible pumps to flexible polyethylene pipes.
- Specifically designed for ground bury applications, it meets the highest standards for durability and safety.
- Featuring an insert barb x male NPT design, it provides a robust connection between your hydrant and flexible polyethylene pipe.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS							
Part No.	Insert Size	x MIP Size	L in.	W in.	H in.	Ctn. Qty.	Approx. Lbs./Ctn.
IBHENL75	3/4"	x 3/4"	2.44	2.13	1.12	10	4.0
IBHENL100	1"	x 3/4"	2.50	2.33	1.15	10	5.0
IBHENL1000	1"	x 1"	2.70	2.24	1.38	10	6.0