

INSERT FITTINGS – MALE ADAPTERS NO-LEAD YELLOW BRASS

SPECIFICATIONS:

- Crafted with precision engineering, this fitting is designed to connect flexible polyethylene pipe to a barbed end and threaded iron pipe to the female end.
- Made from no-lead yellow brass, this fitting provides an economical and easy-to-install solution for connecting well pumps or submersible pumps to flexible pipes.
- Compliant with federal low lead regulations, the no-lead yellow brass male adapter ensures both safety and durability in various plumbing applications.
- Featuring an insert barb x threaded design, it provides a secure and efficient pipe connection.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS						
Part No.	Insert Size	x MIP Size	L in.	W & H in.	Ctn. Qty.	Approx. Lbs./Ctn.
IBMANL50	1/2" x 1/2" Hex		2.41	0.97	10	1.9
IBMANL75	3/4" x 3/4" Hex		2.49	1.2	10	2.3
IBMANL7510	3/4" x 1" Hex		3.13	1.61	10	3.0
IBMANL1075	1" x 3/4" Hex		2.92	1.37	10	3.4
IBMANL100	1" x 1" Round		1.25	1.25	10	2.9
IHBMANL100	1" x 1" Hex		3.48	1.58	10	4.0
IBMANL2510	1-1/4" x 1" Hex		3.36	1.56	10	5.0
IBMANL1025	1" x 1-1/4" Hex		3.33	1.92	10	5.0
IBMANL125	1-1/4" x 1-1/4" Hex		2.76	1.95	10	4.1
IBMANL150	1-1/2" x 1-1/2" Hex		3.09	2.16	5	3.1
IBMANL200	2" x 2" Hex		3.19	2.72	5	5.7