

HEAVY-DUTY (BUILD) STANDARD PRESSURE SWITCHES

SPECIFICATIONS:

- The pressure switch pipe connection features a 1/4" female NPT, providing a reliable and standardized connection.
- Rated at 240 volts and 2HP, this pressure switch is designed for durability and long-lasting performance.
- A heavy fiber board bracket ensures strong contact movement, providing greater heat resistance and durability.
- Extra-large silver contacts extend the switch's service life, while heavy brass wire connections with stainless steel set screws inside a brass tube securely hold up to No. 8 wire.
- Hex stainless steel screws add strength, and a hex wrench is included, conveniently stored inside the base of the switch for easy access.
- Each pressure switch is individually boxed and features a captive nut on the NEMA 1 switch cover.
- Adjustment instructions are located inside the top cover, allowing users to easily adjust settings as needed.




Certified to
NSF/ANSI/CAN 61 & 372



No Lead



U.S. Patent #
D 881,817 and D 949,795



CERTIFICATIONS:

- NSF/ANSI/CAN 61 & 372 Certified

DIMENSIONS							
Part No.	L in.	W in.	H in.	Preset On (PSI)	Preset Off (PSI)	Ctn. Qty.	Approx. Wt./Lbs.
MPSHD2040	3.86	2.80	3.78	ON @ 20 psi (138 kPa)	OFF @ 40 psi (276 kPa)	1	0.90
MPSHD3050	3.86	2.80	3.78	ON @ 30 psi (207 kPa)	OFF @ 50 psi (345 kPa)	1	0.90
MPSHD4060	3.86	2.80	3.78	ON @ 40 psi (276 kPa)	OFF @ 60 psi (414 kPa)	1	0.90
MPSHD6080	3.86	2.80	3.78	ON @ 60 psi (414 kPa)	OFF @ 80 psi (552 kPa)	1	0.90

1/4" NPT SWIVEL UNION - No need to spin switch case						
Part No.	Female x Male	Description	L in.	W & H in.	Ctn. Qty.	Approx. Wt./Lbs.
MPS25UTS	1/4" NPT x 1/4" NPT	Stop Turn Screw	1.60	0.86	1	0.15



TWO POLE ELECTRICAL RATINGS		
Voltage	Single Phase AC	Polyphase AC
115	1-1/2 HP	2 HP
230	2 HP	3 HP



315 Flindt Drive P.O. Box 392
Storm Lake, Iowa 50588-0392 U.S.A.
merrillmfg.com

(800) 831-6962
(712) 732-2760
Fax No. 1-800-ANYFLOW