

EXTRA TALL HEAVY-DUTY PRESSURE SWITCHES

SPECIFICATIONS:

- Built with extra heavy-duty components and weighs 3 lbs., vs. the Competitor's 2 lbs.
- Extra tall case offers more room for heavy wires with its double height design, standing 6" tall, and includes a NEMA 1 case rating.
- Heavy brass wire connections hold No. 4 wire using set screws inside a brass tube, preventing the wires from slipping off the screw.
- Features a 1" knock out for heavy wiring.
- Clear adjustment instructions are provided inside the top cover.
- Contacts open (switch off) at cut-off pressure and points close (switch on) at cut-in or pressure drop.
- A heavy fiber board bracket ensures strong contact movement, providing greater heat resistance and durability.
- Extra-large silver contacts extend the switch's service life.
- Each pressure switch is individually boxed and includes a captive nut on the switch cover.
- A 1/4" swivel union allows for easy installation without the need to pivot the switch case, and a set screw is included to lock the swivel in place.
- A raised grounding lug allows for easy connection and securely holds two wires.



Certified to
NSF/ANSI/CAN 61 & 372

No Lead



U.S. Patent #
10,197,051

CERTIFICATIONS:

- NSF/ANSI/CAN 61 & 372 Certified

DIMENSIONS							
Part No.	L in.	W in.	H in.	Preset On (PSI)	Preset Off (PSI)	Ctn. Qty.	Approx. Wt./Lbs.
MPSXHDT4060	8.35	5.67	6.30	ON @ 40 psi	OFF @ 60 psi	1	3.3
MPSXHDT6080	8.35	5.67	6.30	ON @ 60 psi	OFF @ 80 psi	1	3.3

1/4" NPT SWIVEL UNION - No need to spin switch case							
Part No.	Female x Male	Description	L in.	W & H in.	Ctn. Qty.	Approx. Wt./Lbs.	
MPS25UTS	1/4" NPT x 1/4" NPT	Stop Turn Screw	1.6	0.86	1	0.15	



HEAVY-DUTY ELECTRICAL RATINGS		
Voltage	Single Phase AC	Polyphase AC
115	1/2 HP to 2 HP	3 HP
230	1/2 HP to 3 HP	5 HP
460-600	5 HP	5 HP

Heavy-Duty Switch Rating

- 240 volt single phase 3 HP Pump
- 240/600 volt three phase 5 HP Pump



315 Flindt Drive P.O. Box 392
Storm Lake, Iowa 50588-0392 U.S.A.
merrillmfg.com

(800) 831-6962
(712) 732-2760
Fax No. 1-800-ANYFLOW