

PRESSURE GAUGES

NO LEAD



LEARN MORE ABOUT THE BEST IN THE INDUSTRY AT merrillmfg.com

NO LEAD PRESSURE GAUGES



Certified to
NSF/ANSI/CAN 61 & 372



No-Lead

STANDARD PRESSURE GAUGES

- Temp Range up to 140°F
- No Lead pressure gauges are suitable for water, air, steam, and other pressure applications that will not deteriorate brass alloys. (Individually boxed.)
- No Lead Pressure Gauge Accuracy (+/-3%, +/-2%, +/-3%)

* Back Mount Model

No Lead Pressure Gauges - Plastic Case

Order Number	UPC Bar Code (Qty.1)	Dial Size Inches	Pressure Range	PSI Increments	Connection	Master Ctn. Qty.	Wt. Each Lbs.
PGPNL100	6 42367 41402 3	2"	0-100 psi	2#	1/4" NPT NL Brass - (Lower Male)	100	.18 lbs

No Lead Pressure Gauges - Steel Case

Order Number	UPC Bar Code (Qty.1)	Dial Size Inches	Pressure Range	PSI Increments	Connection	Master Ctn. Qty.	Wt. Each Lbs.
PGNL100	6 42367 09652 6	2"	0-100 psi	2#	1/4" NPT NL Brass - (Lower Male)	100	.22 lbs
*PGBNL100	6 42367 41369 9	2"	0-100 psi	2#	1/8" NPT NL Brass - (Back Mount)	100	.24 lbs
*PGBNL10025	6 42367 41370 5	2"	0-100 psi	2#	1/4" NPT NL Brass - (Back Mount)	100	.24 lbs
*PGBNL160	6 42367 43467 0	2"	0-160 psi	4#	1/8" NPT NL Brass - (Back Mount)	100	.18 lbs
*PGBNL15160	6 42367 42431 2	2"	0-160 psi	4#	1/8" NPT NL Brass - (Back Mount)	100	.20 lbs
*PGBNL16025	6 42367 43547 9	2"	0-160 psi	4#	1/4" NPT NL Brass - (Back Mount)	100	.15 lbs
PGNL15	6 42367 41901 1	2"	0-15 psi	1/5#	1/4" NPT NL Brass - (Lower Male)	100	.22 lbs
PGNL30	6 42367 41365 1	2"	0-30 psi	1/2#	1/4" NPT NL Brass - (Lower Male)	100	.22 lbs
PGNL60	6 42367 09746 2	2"	0-60 psi	1/2#	1/4" NPT NL Brass - (Lower Male)	100	.22 lbs
PGNL160	6 42367 41366 8	2"	0-160 psi	4#	1/4" NPT NL Brass - (Lower Male)	100	.22 lbs
PGNL200	6 42367 09653 3	2"	0-200 psi	4#	1/4" NPT NL Brass - (Lower Male)	100	.22 lbs
PGNL300	6 42367 09978 7	2"	0-300 psi	5#	1/4" NPT NL Brass - (Lower Male)	100	.22 lbs

No Lead Pressure Gauges - Large Diameter - Steel Case

Order Number	UPC Bar Code (Qty.1)	Dial Size Inches	Pressure Range	PSI Increments	Connection	Master Ctn. Qty.	Wt. Each Lbs.
PGNL25100	6 42367 41367 5	2-1/2"	0-100 psi	2#	1/4" NPT NL Brass - (Lower Male)	100	.34 lbs
PGNL25200	6 42367 41368 2	2-1/2"	0-200 psi	4#	1/4" NPT NL Brass - (Lower Male)	100	.34 lbs



PGNL100



PGNL200



PGNL300



PGNL25100





Certified to
NSF/ANSI/CAN 61 & 372



No-Lead

LIQUID FILLED PRESSURE GAUGES

- Temp Range -50°F to 200°F
- For resistance to corrosive atmosphere, vibration and pulsation dampening.
- No Lead liquid filled pressure gauges are suitable for water, air, steam, and other pressure applications that will not deteriorate brass alloys. (Individually boxed.)
- No Lead Liquid Filled Pressure Gauge Accuracy (+/-3%, +/-2%, +/-3%)

* Back Mount Model
= Install in vertical position only

No Lead Liquid Filled Pressure Gauges - Steel Case

Order Number	UPC Bar Code (Qty.1)	Dial Size Inches	Pressure Range	PSI Increments	Connection	Master Ctn. Qty.	Wt. Each Lbs.
Ⓢ =PGLNL1002	6 42367 41401 6	2"	0-100 psi	2#	1/4" NPT NL Brass - (Lower Male)	100	.30 lbs
Ⓢ* =PGLBNL100	6 42367 41375 0	2"	0-100 psi	2#	1/4" NPT NL Brass - (Back Mount)	100	.30 lbs

No Lead Liquid Filled Pressure Gauges - 300 Stainless Steel Case

Order Number	UPC Bar Code (Qty.1)	Dial Size Inches	Pressure Range	PSI Increments	Connection	Master Ctn. Qty.	Wt. Each Lbs.
Ⓢ =PGLNL30	6 42367 41371 2	2-1/2"	0-30 psi	1/2#	1/4" NPT NL Brass - (Lower Male)	50	.42 lbs
Ⓢ =PGLNL60	6 42367 41372 9	2-1/2"	0-60 psi	1#	1/4" NPT NL Brass - (Lower Male)	50	.42 lbs
Ⓢ =PGLNL100	6 42367 09661 8	2-1/2"	0-100 psi	2#	1/4" NPT NL Brass - (Lower Male)	50	.42 lbs
Ⓢ =PGLNL160	6 42367 09662 5	2-1/2"	0-160 psi	5#	1/4" NPT NL Brass - (Lower Male)	50	.42 lbs
Ⓢ =PGLNL200	6 42367 09663 2	2-1/2"	0-200 psi	2#	1/4" NPT NL Brass - (Lower Male)	50	.42 lbs
Ⓢ =PGLNL300	6 42367 09664 9	2-1/2"	0-300 psi	5#	1/4" NPT NL Brass - (Lower Male)	50	.42 lbs
Ⓢ =PGLNL600	6 42367 43322 2	2-1/2"	0-600 psi	10#	1/4" NPT NL Brass - (Lower Male)	50	.40 lbs

No Lead Liquid Filled Pressure Gauges - 300 Stainless Steel Case - Back Mount

Order Number	UPC Bar Code (Qty.1)	Dial Size Inches	Pressure Range	PSI Increments	Connection	Master Ctn. Qty.	Wt. Each Lbs.
Ⓢ* =PGLBNL25100	6 42367 41373 6	2-1/2"	0-100 psi	2#	1/4" NPT NL Brass - (Back Mount)	50	.40 lbs
Ⓢ* =PGLBNL25200	6 42367 41400 9	2-1/2"	0-200 psi	4#	1/4" NPT NL Brass - (Back Mount)	50	.45 lbs
Ⓢ* =PGLBNL25300	6 42367 43249 2	2-1/2"	0-300 psi	5#	1/4" NPT NL Brass - (Back Mount)	50	.45 lbs

Stainless Steel Connection Liquid Filled Pressure Gauges - 304 Stainless Steel Case

Order Number	UPC Bar Code (Qty.1)	Dial Size Inches	Pressure Range	PSI Increments	Connection	Master Ctn. Qty.	Wt. Each Lbs.
Ⓢ =PGLSSNL30	6 42367 43222 5	2-1/2"	0-30 psi	1/2#	1/4" NPT NL Brass - (Lower Male)	50	.43 lbs
Ⓢ =PGLSSNL100	6 42367 43223 2	2-1/2"	0-100 psi	2#	1/4" NPT NL Brass - (Lower Male)	50	.43 lbs
Ⓢ =PGLSSNL160	6 42367 43224 9	2-1/2"	0-160 psi	4#	1/4" NPT NL Brass - (Lower Male)	50	.43 lbs
Ⓢ* =PGLBSSNL100	6 42367 43225 6	2-1/2"	0-100 psi	2#	1/4" NPT NL Brass - (Back Mount)	50	.43 lbs




PGLBNL100



PGLNL200



PGLBNL25300



PGLSSNL30



© 2024 Merrill Manufacturing Form No. 2128.5
315 Flindt Dr. | Storm Lake, Iowa 50588 | (800) 831-6962 | merrillmfg.com