

PTFE TEFLON® GRAY THREAD SEAL TAPE FOR STAINLESS STEEL WITH NICKEL - HIGH DENSITY

SPECIFICATIONS:

- The gray thread tape contains nickel powder, which helps flow and fill gaps between the rigid threads of stainless steel and no lead brass fittings. This additive is strongly recommended for use with stainless steel, distinguishing it from lower-priced alternatives that may only offer gray color without the essential nickel content.
- High density tape prevents it from being “cut up” when wrapped around the sharp threads. It can also be stretched slightly to stay securely in place.
- It’s thickness insures fewer warp are needed for a leak-proof seal, unlike lower cost and lower quality tapes that are thinner and can be easily cut through when tightened, this tape is the right thickness to create a reliable seal.
- Extra width of tape is offered to match the size of the fittings. Larger pipe fittings require wider tape for effective sealing without needing excessive amounts of tape or taking more time to apply.
- Compatible with quality thread sealants like AQUA-SEAL. When applied on top of the gray PTFE tape, AQUA-SEAL flows and fills gaps between threads.
- When the tape and AQUA-SEAL is used together, it provides a strong, tight seal for threaded joints that can be easily disassembled when needed. AQUA-SEAL is a soft set sealant that will not crack and provides a long-lasting seal for years.



No Lead

DIMENSIONS				
Part No.	Description	Thickness	Carton Qty.	Approx. Wt./Lbs.
PTFEGSS50260	1/2" x 260" Long	0.004"	100	0.04
PTFEGSS50520	1/2" x 520" Long	0.004"	100	0.05
PTFEGSS75260	3/4" x 260" Long	0.004"	100	0.04

MATERIALS LIST	
Part Name	Material
Gray Thread Tape	Nickel Powder and PTFE Teflon®