

PRESSURE RELIEF VALVES PVC (DARK GREY)

SPECIFICATIONS:

- Constructed from heavy-duty PVC, this pressure relief valve is built for durability and designed for cold water systems.
- The valve is a perfect companion to Merrill PVC Tank Tees 100C, 100CS, 100CSF, and 1025CSF.
- The valve features a lubricated seal to prevent sticking and is factory preset at 75 psi with a $\pm 15\%$ setting accuracy.
- While not intended for use as temperature and pressure valves for water heaters, these valves are essential for protecting cold water pressure tanks and piping. The warranty is void if they are used on air systems.
- To prevent valve chatter or rapid opening and closing, set the valve at least 15 psi above the typical maximum system pressure. Chatter can cause valve failure and void the warranty.
- Designed for low maintenance, the relief pressure is easy to adjust with a screwdriver. The valve is adjustable up to 150 psi, but any adjustments void the warranty due to the potential for errors.
- The PVC pressure relief valve has been 100% factory tested.



No Lead



DIMENSIONS

Part No.	Inlet x Outlet	L in.	W in.	H in.	Ctn. Qty.	Ctn. Wt./Lbs.
PVCPRV50	1/2" MIP x 1/2" FIP	2.47	1.63	1.43	1	.20