

INSERT FITTINGS – ELBOWS

NO-LEAD BRONZE

SPECIFICATIONS:

- Crafted with precision engineering, this 90-degree barb x barb elbow features a sturdy flat bottom base, ensuring a seamless and secure pipe-to-pipe connection, setting the standard in precision and reliability.
- Made from heavy-duty no-lead bronze, this fitting complies with federal low lead regulations and provides an economical, easy-to-install solution for connecting well pumps or submersible pumps to flexible polyethylene pipes.
- The 90-degree insert barb x insert barb design, it provides a secure and efficient connection.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS								
Part No.	Insert Size	x	Insert Size	L in.	W in.	H in.	Ctn. Qty.	Approx. Lbs./Ctn.
RBDENL75	3/4"	x	3/4"	2.44	2.42	1.00	10	3.6
RBDENL100	1"	x	1"	2.51	2.49	1.21	10	4.5
RBDENL125	1-1/4"	x	1-1/4"	3.28	3.28	1.62	10	9.0
RBDENL1025	1-1/4"	x	1"	3.33	3.19	1.63	10	8.4
BDENL150	1-1/2"	x	1-1/2"	3.52	3.51	1.85	10	15.0