

# INSERT FITTINGS – MALE ADAPTERS

## NO-LEAD BRONZE

### SPECIFICATIONS:

- Crafted with precision engineering, this no-lead bronze fitting is designed to connect flexible polyethylene pipe to a barbed end and a female NPT thread to the male end, providing a secure and reliable connection.
- Made from durable, corrosion-resistant no-lead bronze, this fitting offers an economical and easy-to-install solution for connecting well pumps or submersible pumps to flexible pipes.
- Compliant with federal low lead regulations, the no-lead bronze male adapter ensures both safety and durability in various plumbing applications.
- The insert barb x threaded design allows for a secure and efficient pipe connection. The hex design provides an easier grip during installation.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified



### CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS						
Part No.	Insert Size	X MIP Size	L in.	W & H in.	Ctn. Qty.	Approx. Lbs./Ctn.
RBMANL50	1/2"	x 1/2"	2.56	1.02	10	1.6
RBMANL75	3/4"	x 3/4"	2.54	1.28	10	2.2
RBMANL7510	3/4"	x 1"	2.76	1.58	10	3.0
RBMANL1075	1"	x 3/4"	2.88	1.38	10	2.8
RBMANL100	1"	x 1"	3.52	1.60	10	4.2
RBMANL2510	1-1/4"	x 1"	3.39	1.55	10	5.2
RBMANL1025	1"	x 1-1/4"	3.17	1.81	10	4.5
RBMANL125	1-1/4"	x 1-1/4"	3.16	1.85	10	5.5
RBMANL150	1-1/2"	x 1-1/2"	3.22	2.14	5	3.4
RBMANL200	2"	x 2"	3.30	2.82	5	5.7