


GEO THERMAL UNION ADAPTERS RED BRASS – INSERT FITTINGS



SPECIFICATIONS:

- **WARNING:** This product can expose you to lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. (For more information go to www.p65warnings.ca.gov)
- The leaded red brass geo thermal union adapter features a 1/4" tapping with an O-ring and a plastic pipe to male iron pipe (MIP) connection.
- Its insert barb x male NPT design ensures a secure and efficient pipe connection, while the wide-width hex accommodates wrenches for easier installation.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



DIMENSIONS								
Part No.	Insert Size	x	MIP Size	L in.	W in.	H in.	Ctn. Qty.	Approx. Lbs./Ctn.
RGSEU7525	3/4"	x	3/4"	3.55	2.69	1.69	5	3.9
RGSEU10025	1"	x	1"	4.09	3.13	2.08	5	5.3
RGSEU12525	1-1/4"	x	1-1/4"	4.70	3.39	2.36	5	7.3
RGSEU751025	1"	x	3/4"	4.17	3.04	2.07	5	4.0
RGSEU1001225	1-1/4"	x	1"	4.64	3.26	2.36	5	5.4



WARNING: This product can expose you to lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. (For more information go to www.p65warnings.ca.gov)