

# STEEL INSERT FITTINGS – MALE ADAPTERS

## ZINC-PLATED

### SPECIFICATIONS:

- Crafted with precision engineering, the plastic pipe to male iron pipe, zinc-plated steel male adapter connects flexible polyethylene pipes to the barbed end, while the male end fits securely into a female NPT thread.
- Designed for secure connections, this fitting ensures a smooth transition, making it an ideal choice for a wide range of plumbing applications.
- The steel fitting is zinc-plated for corrosion resistance and can withstand high pressure, ensuring long-lasting and reliable performance
- Featuring an insert barb x threaded design, it provides a secure and efficient pipe connection.
- Its economical design provides a cost-effective solution for both residential and professional plumbing needs.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

### CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS							
Part No.	Insert Size	x	MIP Size	L in.	W & H in.	Ctn. Qty.	Est. Lbs./Ctn.
SMA50	1/2"	x	1/2"	3.17	0.86	25	3.5
SMA75	3/4"	x	3/4"	3.22	1.06	25	5.0
SMA100	1"	x	1"	3.58	1.33	20	6.0
SMA125	1-1/4"	x	1-1/4"	3.74	1.69	20	10.0
SMA150	1-1/2"	x	1-1/2"	4.28	1.91	10	6.8
SMA200	2"	x	2"	4.37	2.38	10	8.6
SMA300	3"	x	3"	6.09	3.50	4	10.6
SMA400	4"	x	4"	7.44	4.48	2	8.7