

SMCK – PITLESS KITS STAINLESS STEEL

SPECIFICATION:

- Tested and approved by Pitless Adapter Standard PAS-1, PAS-2, PAS-97(2019) (R 2023), ASSE Standard #1093-2019(R 2023), and Illinois Code.
- By simply turning the stainless steel adjusting nut at the top of the well, it enables a positive mechanical seal. This assures reliable sealing and allows for easy disengagement for service without pulling the pump.
- No obstructions inside the well that may need to be removed before working on well, providing a simple and fast installation.
- Large thick O-ring seal assures a watertight seal around the hole cut in the casing, while the all stainless steel discharge hub clamps around the casing with a all stainless steel U-strap to prevent distortion of plastic casing if overtightened.
- The 3 part kit consists of discharge hub, internal parts, and ventilated or watertight cap.
- Allows use of existing plastic or steel casing with no restrictions on materials.
- The heavy duty galvanized iron support plate holds 160% more weight than aluminum support bar by other manufacturers, and holds more weight than slide together type pitless adapters. The weight of the pump, pipe, and water is supported by the bar, minimizing the danger of losing the pump or pipe down well. Merrill support bar also has a ground screw.
- Easily drain the water system by turning the stainless steel nut at the top of the well, so the entire water system outside the well can be drained without pulling the pump.
- Stainless steel elbow fitting is available for discharge.



C.A. Certified



Note: Illinois State Approved



CERTIFICATIONS:

- PAS-1, PAS-2, PAS-97(2019)(R 2023)
- ASSE Standard #1093-2019(R 2023)
- IAPMO CA. Certified
- Illinois Code
- Max Pressure: 120 PSI
- Max Temperature: 120°F

MATERIAL LIST	
Part Name	Material
Support Bar	Galvanized Iron
Thumb Screw	Stainless Steel
Internal Pitless Body	Stainless Steel
Flipper	Stainless Steel
Pivot Pin	Stainless Steel
Discharge Hub w/O-Ring	Stainless Steel
O-Ring Seal	Buna
U-Strap w/Nuts	Stainless Steel

DIMENSIONS				
Part No.	Well Size I.D./O.D.	Drop Pipe & Discharge	Hole Saw	Weight (lbs)
SMCK410	4.0"/4.5"	1"	1"	7.7
SMCK414	4.0"/4.5"	1-1/4"	1-1/4"	7.5
SMCK510	5.0"/5.6"	1"	1"	9.3
SMCK514	5.0"/5.6"	1-1/4"	1-1/4"	8.9
SMCK610	6.0"/6.6"	1"	1"	11.1
SMCK614	6.0"/6.6"	1-1/4"	1-1/4"	10.3



315 Flindt Dr. | Storm Lake, Iowa 50588
(800) 831-6962 | merrillmfg.com