

304 STAINLESS STEEL BALL VALVES

SPECIFICATIONS:

- Constructed from all 304 stainless steel, these ball valves offer excellent strength and corrosion resistance.
- They allow for easy flow adjustment or positive shutoff.
- The full port design ensures maximum flow, while the chrome plated ball enhances durability.
- Teflon® seals provide a reliable and secure seal.
- The handle is lockable for added safety and security, and the all stainless steel construction ensures long-lasting performance.



No Lead

RATINGS

- WOG Rating: 1000 W.O.G.
- Max Temp: 212°F

DIMENSIONS						
Part No.	Thread Size x Thread Size	L in.	W in.	H in.	Ctn. Qty.	Approx. Wt./Lbs.
SSBV50	1/2" x 1/2"	5.40	2.75	1.50	12	0.9
SSBV75	3/4" x 3/4"	6.00	3.40	1.70	10	0.8
SSBV100	1" x 1"	6.75	3.70	2.00	6	1.9
SSBV125	1-1/4" x 1-1/4"	8.25	4.35	2.75	4	2.0
SSBV150	1-1/2" x 1-1/2"	8.40	4.75	3.00	1	2.0
SSBV200	2" x 2"	10.25	5.80	3.30	2	5.3

MATERIALS LIST	
Part Name	Material
Valve Body	304 Stainless Steel
Ball	Chrome Plated
Seals	Teflon®
Handle	304 Stainless Steel
Locking Device	304 Stainless Steel