


# INSERT FITTINGS – HYDRANT ELBOWS

## 304 STAINLESS STEEL

### SPECIFICATIONS:

- Crafted with precision engineering, this barb x male NPT 90-degree elbow ensures a seamless and secure pipe-to-pipe connection, setting the standard in precision and reliability.
- The sturdy flat bottom base enhances stability, while the full-length set of insert barbs ensures a reliable and durable connection.
- The solid casting construction provides both strength and economy.
- Made from all 304 stainless steel, the fitting offers corrosion resistance, ensuring long-lasting and reliable performance.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

### CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS							
Part No.	Insert Size x MIP Size	L in.	W in.	H in.	Ctn. Qty.	Est. Lbs./Ctn.	
SSHE75	3/4" x 3/4"	2.44	2.02	1.14	10	0.5	
SSHE100	1" x 3/4"	2.78	2.34	1.23	10	0.7	
SSHE1000	1" x 1"	2.78	2.34	1.23	10	0.6	
SSHE1025	1-1/4" x 1"	3.25	2.53	1.67	5	0.8	
SSHE125	1-1/4" x 1-1/4"	3.23	2.61	1.59	5	0.9	