

INSERT FITTINGS – HYDRANT TEES

304 STAINLESS STEEL

SPECIFICATIONS:

- Crafted with precision engineering, this insert barb x male NPT x insert barb hydrant tee ensures secure and stable connections, providing a seamless multi-pipe connection, setting the standard in precision and reliability.
- Designed with a full-length set of insert barbs, this fitting ensures a secure connection.
- The solid casting construction provides both strength and economy, while the sturdy flat bottom base enhances stability and allows easy installation with a wrench.
- Made from all 304 stainless steel, the fitting offers corrosion resistance, ensuring long-lasting and reliable performance.
- Hose clamps (sold separately) ensure a secure and easy installation.
- The maximum pressure and temperature ratings depend on the material and specifications of the pipe used, ensuring compatibility with diverse systems.



No Lead



C.A. Certified

CERTIFICATIONS:

- IAPMO CA. Certified

DIMENSIONS										
Part No.	Insert Size	x	MIP Size	x	Insert Size	L in.	W in.	H in.	Ctn. Qty.	Approx. Lbs./Ctn.
SSHT75	3/4"	x	3/4"	x	3/4"	3.35	2.07	1.15	10	0.5
SSHT7510	1"	x	3/4"	x	1"	4.18	2.06	1.15	10	0.6
SSHT100	1"	x	1"	x	1"	3.60	2.27	1.37	10	0.7
SSHT10125	1-1/4"	x	1"	x	1-1/4"				5	0.7