

# INSERT 304 STAINLESS STEEL BALL VALVES

## SPECIFICATIONS:

- Designed for use with polyethylene (PE) pipe, these insert stainless steel ball valves feature an insert barb x insert barb connection.
- They allow for easy flow adjustment or positive shutoff.
- The full port design ensures maximum flow through the insert ends and ball.
- The chrome plated ball enhances durability, while the Teflon® seals provide a reliable and secure seal.
- Constructed from 304 stainless steel, these valves offer excellent strength and corrosion resistance.



No Lead



| DIMENSIONS |             |   |             |                |                   |                |           |                  |
|------------|-------------|---|-------------|----------------|-------------------|----------------|-----------|------------------|
| Part No.   | Insert Size | x | Insert Size | Overall Length | Valve Body Length | Overall Height | Ctn. Qty. | Approx. Wt./Lbs. |
| SSVI75     | 3/4"        | x | 3/4"        | 6.125"         | 4.300"            | 2.750"         | 10        | 0.8              |
| SSVI100    | 1"          | x | 1"          | 6.500"         | 4.860"            | 2.625"         | 10        | 1.2              |
| SSVI125    | 1-1/4"      | x | 1-1/4"      | 7.375"         | 5.275"            | 3.500"         | 5         | 1.6              |

| MATERIALS LIST |                     |
|----------------|---------------------|
| Part Name      | Material            |
| Valve Body     | 304 Stainless Steel |
| Ball           | Chrome Plated       |
| Seals          | Teflon®             |