

# 1-1/4" NO-LEAD BRASS TANK TEE PACKAGES

## SPECIFICATIONS:

- BATNL1252XUC: No-lead brass tank tee with union, 1-1/4" MIP tank connection, 1-1/4" MIP & 1" FIP laterals, two 3/4" drain holes, and 14" length.
- BBDNL75MS: 3/4" MIP No-Lead Brass Boiler Drain, other drain valves available.
- PGNL100: 0-100 psi No-Lead Pressure Gauge, steel case, 1/4" lower male no-lead brass connection.
- PRVNL75100: 3/4" No-Lead Pressure Relief Valve, factory pressure setting at 100psi.
- CVNL125: Only models TPBNL1252XUCA and TPBNL1252XUCA4 include a 1-1/4" No-Lead Brass Check Valve.
- BNNL2503: 1/4" x 3" No-Lead Brass Nipple.
- IBMANL125: Only models TPBNL1252XUCA and TPBNL1252XUCA4 include a 1-1/4" No-Lead Brass Insert Fitting.
- BBVNL125: Some models include a 1-1/4" No-Lead Brass Ball Valve.
- MPS3050: Some models include a 30/50 Pressure Switch, 1/4" female NPT connection.
- MPS4060: Some models include a 40/60 Pressure Switch, 1/4" female NPT connection.
- PTFEWH5060: 1/2" x 60" White Teflon® Thread Tape.
- Tank fitting packages can be packaged in any combination of components.



No Lead



C.A. Certified



## CERTIFICATIONS:

- IAPMO CA. Certified

PRODUCT DETAILS						
Part No.	Tank Tee	Pressure Switch	Check Valve	Insert Fitting	Ball Valve	Approx. Wt./Lbs.
TPBNL1252XUCA	BATNL1252XUC with Union	30/50	Included	Included	Included	8.5
TPBNL1252XUCA4	BATNL1252XUC with Union	40/60	Included	Included	Included	8.5
TPBNL1252XUCB	BATNL1252XUC with Union	30/50	Not Included	Not Included	Included	7.0
TPBNL1252XUCB4	BATNL1252XUC with Union	40/60	Not Included	Not Included	Included	7.0
TPBNL1252XUCC	BATNL1252XUC with Union	30/50	Not Included	Not Included	Not Included	5.4
TPBNL1252XUCC4	BATNL1252XUC with Union	40/60	Not Included	Not Included	Not Included	5.4

**Note:** All 1-1/4" No-Lead Brass Tank Tee Packages include a No-Lead Brass Boiler Drain, No-Lead Pressure Gauge, No-Lead Brass Pressure Relief Valve, No-Lead Brass Nipple, and White Teflon® Thread Tape.