

ABS RESIN – WATERTIGHT WELL CAPS



SPECIFICATIONS:

- All caps certified watertight - Pitless Adapter Standard PAS-2, PAS-97(2019) (R 2023), ASSE Standard #1093-2019(R 2023) and Illinois Code.
- The watertight well cap provides protection to the exposed portion of the well casing by being tamper-resistant, forming a protective cover from the elements, and being resistant to the entry of vermin or contaminants.
- Designed for use with all pitless adapters, the cap fits a 6” IPS casing with a 1-1/4” IPS conduit tap, ensuring a secure and watertight seal.
- Made from hi-impact ABS resin, the cap offers excellent durability and is resistant to impact, ensuring reliable performance even in tough conditions.
- The cap is vermin proof, protecting the system from unwanted pests from entering and potentially compromising its integrity.
- Formulated for outdoor weatherability, it is designed to withstand harsh environmental conditions, ensuring long-lasting performance.



CERTIFICATIONS:

- PAS-2 and PAS-97(2019)(R 2023)
- ASSE Standard #1093-2019(R 2023)
- Illinois Code

MATERIALS LIST	
Part Name	Material
Cap Cover	Molded ABS Resin
Rubber Gasket	Neoprene
Rubber Seal	Neoprene
Clamping Ring	Molded ABS Resin
Bolts, Washers, & Nuts	Stainless Steel
Hex Bolt w/Nuts (6)	Plated Steel

DIMENSIONS					
Part No.	Casing I.D. Size	Casing O.D. Size	Conduit Tap Size	Vent Size	Approx. Wt./Lbs.
WCABS400	4”	4-1/2”	1-1/4” IPS	7/16”	2.2
WCABS600	6”	6-5/8”	1-1/4” IPS	7/16”	4.0