


WCB SERIES – SANITARY (WATERTIGHT) CAPS

SPECIFICATIONS:

- All caps certified watertight - Pitless Adapter Standard PAS-2, PAS-97(2019) (R 2023), ASSE Standard #1093-2019(R 2023) and Illinois Code.
- The watertight well cap provides protection to the exposed portion of the well casing by being tamper-resistant, forming a protective cover from the elements, and being resistant to the entry of vermin or contaminants.
- Designed for use with all pitless units and adapters.
- Made from painted cast iron, for long-lasting performance.
- Plated bolts provide a strong secure, corrosion-resistant connection.
- Wide compression gasket ensures a reliable, watertight seal.
- Each cap is individually boxed.



CERTIFICATIONS:

- PAS-2 and PAS-97(2019)(R 2023)
- ASSE Standard #1093-2019(R 2023)
- Illinois Code

MATERIALS LIST	
Part Name	Material
Cap Casting	Painted Cast Iron
Square Head Bolts w/Nuts	Zinc Plated
Square Head Plug	Galvanized Gray Iron
Flat Gasket	Neoprene
Retainer Ring Casting	Painted Cast Iron
Rubber Gasket	Neoprene
Clamping Ring Casting	Painted Cast Iron

DIMENSIONS					
Part No.	Casing I.D. Size	Casing O.D. Size	Conduit Tap Size	Vent Size	Approx. Wt./Lbs.
WCB400	4"	4-1/2"	1-1/2"	1"	14.3
WCB500	5"	5-9/16"	1-1/2"	1"	15.9
WCB600	6"	6-5/8"	1-1/2"	1-1/4"	24.1
WCB800	8"	8-5/8"	1-1/2"	2"	39.3
WCB100	10"	10-3/4"	3"	2-1/2"	58.6
With Grounding Screw					
WCBG400	4"	4-1/2"	1-1/2"	1"	14.3
WCBG500	5"	5-9/16"	1-1/2"	1"	15.9
WCBG600	6"	6-5/8"	1-1/2"	1-1/4"	24.1
WCBG800	8"	8-5/8"	1-1/2"	2"	39.3
WCBG100	10"	10-3/4"	3"	2-1/2"	58.6